

FOGMAKER

South Africa

Automatic fire suppression system protecting Aircraft Ground Equipment (AGE)

TRIPLE ACTION³

With high-pressure water mist.





FPASA

(Fire Protection Association of Southern



ISO 9001 and 14001

(Quality and Environmental Management System)



AS-5062

(Australian Standards)



(International Standard for Automotive Quality Management Systems)



UL listed 1384

(American Standard for Mining Equipment)



FIA

(International Automobile Federation)



UNECE

(UN R-107 Vehicle Regulation)



SBF 127

(Certified for Logging and Construction)





(Certified for Buses and Coaches)



SPCR 197 / 183

(Swedish Fire Protection Association)



SAMSA

(South Africa Maritime Safety Authority)



(Bureau Veritas - Marine and Offshore)



(Certification for Ship's Components and Accessories)



(Swedish Maritime Administration)



(Worldwide Standards for Manufacturers -



FOGMAKER's fire suppression system effectively attacks all three sides of the fire triangle. We call this unique performance Triple Action³.

Micro droplets of water-based extinguishant are generated by patented nozzles under high pressure. These droplets flood the area being protected and evaporate immediately on contact with heat. During the evaporation process, 1 litre of water will expand into 1700 litres of water vapour, which displaces air and stops the oxygen supply to the fire.

During the vaporization process the water mist cools the hot gases and hot surfaces in the engine compartment. It takes 1 calorie to heat up 1 gram of water by 1°C, but 540 times more energy to evaporate the same amount of water. The cooling achieved by this vaporization reduces the risk of re-ignition.


FOGMAKER's suppressant also includes, in low concentrations, an Aqueous Film Forming Foam (AFFF), which forms a protective barrier on the surface of any flammable material or fuel, thus preventing the fuel from being available for combustion.

Due to the nature of the working environment, forestry machines are at a high risk of fire. Accumulated flammable organic debris in hot areas within the engine compartment is by far the most common cause of fires in forestry equipment, followed by electrical faults.

An engine fire can be devastating, as every minute of the operation counts, and forestry operations are extremely sensitive to unscheduled downtime.

Due to the typically large quantities of diesel and hydraulic oil, often operating under high pressure in the immediate area, an ignited engine fire could lead to a rapid and disastrous series of events.

The financial and operational consequences have the potential to affect everyone, from the operator to the contractor to the insurer, as well as the landowner.





ASSET PROTECTION


Mitigating the risk of an engine fire with FOGMAKER's automatic fire suppression system is the best way to protect your fleet of valuable assets from the threat of fire. FOGMAKER is fast becoming the fire protection solution of choice, and is trusted by many owners of heavy vehicles and mobile industrial machinery to safeguard their machines, save operator lives and protect the environment in which they are working. The FOGMAKER fire suppression system is developed and manufactured in Sweden. FOGMAKER has a successful global track record in Europe, Australia, North and South America, Middle East and Africa – with over 200,000 units installed worldwide since 1995.



Fire suppression test in a simulated engine compartment with a volume of 2.5 m³. The fire source consists of Four 20cm x 40cm trays filled with diesel. A spray fire is then simulated by applying diesel at a rate of 2 litres per minute at a pressure of 5 bar, which engulfs the engine. The combined heat output of the fire is approximately 1600 kW








In this simulation the fire is allowed to burn for more than 20 seconds. The burnt gas temperature increases to 870 °C at which point the FOGMAKER system is activated manually. In 10 seconds the temperature of the burnt gases decreases to approximately 136 °C. In addition to the rapid extinguishing the risk of re-ignition is minimized. This means reduced repairs and downtime.

WHY FOGMAKER?

- Extremely effective Triple Action³ fire suppression system attacks all 3 sides of a fire triangle.
- Automatic fire suppression system using loss of pressure (LOP) technology. No electric power required.
- Simplicity Minimal obstruction, low weight and orientation independent.
- Easily installed within one working day by our
 FOGMAKER Field Engineers.
- Low life-cycle cost Periodic inspections and major service every 2 years (MHSA) or 3 years (PER).
- System monitoring including low pressure and fire alarm.
- Automatic engine shut down optional.
- Easy clean-up and quick recharge once system has been triggered.





amazing team who are passionate about our product and the customers we service. What truly differentiates us from our competition is our approach to risk mitigation, our tailored system design, our speedy installation and excellent after-sales service. Our mobile technical consulting team are available to visit you on-site to conduct fire risk assessments,

installations and servicing.

Head office Address: 5 Jansen Road, Witfield, Boksburg, 1459, Gauteng.

Tel: +27 (11) 894 2906 Email: info@fogmaker.co.za Website: www.fogmaker.co.za Johannesbur Steelpoort Rustenburg Durban Cape Town Zambia Botswana

